

2005 TEAM GREEN RECOMMENDED SUSPENSION CHART

Rider Weight	Fork Position (height)*	FRONT FORKS						REAR SHOCK					
		Spring Rate	Oil Level	Oil Weight	Reb Out	Comp Out	Spring Rate	Preload/SAG Level	Reb Out	Comp Out Low	Nitro Pressure		
KX65-A6													
												Pull Rods	
55-65	15mm	0.26	Light	130mm	10	2****	n/a	4.7	Light	70mm	2****	**STK	140psi
65-75	10mm	0.27	Stock	130mm	10	2****	n/a	4.9	Stock	70mm	1.5****	**STK	140psi
75-85	Flush	0.28	Heavy	125mm	10	3****	n/a	4.9	Stock	70mm	1****	85.3mm	140psi
KX85-A5													
Up to 75	Std	0.27	Ex Light	90mm	5	n/a	8	4.4	Extra Light	80-85mm	9	1	150psi
75-100	Std	0.28	Light	90mm	5	n/a	8	4.6	Light	80-85mm	9	1	150psi
100-115	Std	0.29	Stock	90mm	5	n/a	8	4.8	Stock	80-85mm	8	1	150psi
115-125	Std	0.30	Heavy	80mm	5	n/a	8	5.0	Heavy	80-85mm	8	2	150psi
KX100-D5													
70-85	Std	0.27	Ex Light	90mm	5	n/a	8	4.4	Ex Light	80-85mm	9	2	150psi
85-100	Std	0.28	Light	90mm	5	n/a	8	4.6	Light	80-85mm	9	2	150psi
100-115	Std	0.29	Stock	90mm	5	n/a	8	4.8	Stock	80-85mm	8	2	150psi
115-125	Std	0.30	Heavy	80mm	5	n/a	8	5.0	Heavy	80-85mm	8	2-3	150psi
KX125-M3													
130-145	10mm	.41	Light	90mm	5	14	6-10	4.5***	Ex Light***	100-105mm	13	14-18	150psi
145-165	10mm	.42	Stock	90mm	5	12	6-10	4.7	Light	100-105mm	12	14-18	150psi
165-175	10mm	.43	Heavy	95mm	5	12	6-10	4.9	Stock	100-105mm	12	14-18	150psi
KX250F-N2													
130-150	5mm	.43	Light	90mm	5	12	6-10	4.7	Ex Light	102-105mm	12	12-16	150psi
150-170	5mm	.44	Stock	90mm	5	12	6-10	4.9	Light	102-105mm	12	12-16	150psi
170-190	5mm	.45	Heavy	95mm	5	10	6-10	5.1	Stock	102-105mm	11	12-16	150psi
K250-R1X													
130-150	5mm	.44	Light	300cc	5	14	5-10	5.1	Light	102-105mm	8	12-16	150psi
150-170	5mm	.45	Stock	310cc	5	14	5-10	5.3	Stock	102-105mm	7	12-16	150psi
170-190	5mm	.46	Heavy	310cc	5	12	5-10	5.5	Heavy	102-105mm	7	12-16	150psi
KX200-H11 & KDX220-A12													
135-150	Std	0.34	Light	95mm	5	n/a	8-10	4.8	Light	100mm	9	10	150psi
150-170	Std	0.35	Stock	95mm	5	n/a	8-10	5.0	Stock	100mm	9	10	150psi
170-200	Std	0.36	Heavy	95mm	5	n/a	8-10	5.2	Heavy	100mm	9	10	150psi
200+	Std	0.37	Xtra Heavy	95mm	5	n/a	8-10	5.4	Xtre Heavy	100mm	9	10	150psi
KLX300-A10													
All weights	Std	0.38	n/a	95mm	5	n/a	14	5.8	Stock	100mm	9	12	150psi

*Fork Height is measured from top of fork tube to top of fork clamp.

**Stock 86.3mm pull rods on the 2002 KX65 can be exchanged for optional 85.3mm or 87.3mm to raise or lower the seat height by 4.5mm each.

***Optional spring from a previous year KX125 Part number 92144-1501-45.

****Refer to the 2003 KX65 owners manual for position information.

FOOTNOTES - Rebound and compression adjustments are the number of clicks out from full hard (all the way in). Front fork oil level is measured in millimeters (mm). Rear shock sag level is measured in millimeters (mm). All optional spring part numbers can be found at your local Kawasaki dealership. SPECIAL NOTE - Team Green recommends that any suspension setting changes be done at normal riding temperatures. Always test new settings before racing. *Team Green Specifications subject to change.