



## 2002 TEAM GREEN RECOMMENDED SUSPENSION CHART

		FRONT FORKS						REAR SHOCK					
Rider Weight	Fork Position (height)*	Spring Rate	Oil Level	Oil Weight	Reb Out	Comp Out	Spring Rate	Preload/SAG Level	Reb Out	Comp Out Low	Comp Out High**	Nitro Pressure	
KX60-B18													
50-70	Std	0.23	130mm	10	n/a	n/a	3.0	#4	n/a	n/a	n/a	n/a	
70-90	Std	0.25	130mm	10	n/a	n/a	3.3	#3	n/a	n/a	n/a	n/a	
90+	Std	0.27	130mm	10	n/a	n/a	3.7	#2	n/a	n/a	n/a	n/a	
KX65-A3													
55-65	15mm	0.26	130mm	10	2****	n/a	4.7	70mm	2****	**STK	n/a	140psi	
65-75	10mm	0.27	130mm	10	2****	n/a	4.9	70mm	1.5****	**STK	n/a	140psi	
75-85	Flush	0.28	125mm	10	3****	n/a	4.9	70mm	1****	85.3mm	n/a	140psi	
KX85-A2													
Up to 75	Std	0.27	90mm	5	n/a	8	4.4	80-85mm	9	1	n/a	150psi	
75-100	Std	0.28	90mm	5	n/a	8	4.6	80-85mm	9	1	n/a	150psi	
100-115	Std	0.29	90mm	5	n/a	8	4.8	80-85mm	8	1	n/a	150psi	
115-125	Std	0.30	80mm	5	n/a	8	5.0	80-85mm	8	2	n/a	150psi	
KX100-D2													
70-85	Std	0.27	90mm	5	n/a	8	4.4	80-85mm	9	2	n/a	150psi	
85-100	Std	0.28	90mm	5	n/a	8	4.6	80-85mm	9	2	n/a	150psi	
100-115	Std	0.29	90mm	5	n/a	8	4.8	80-85mm	8	2	n/a	150psi	
115-125	Std	0.30	80mm	5	n/a	8	5.0	80-85mm	8	2-3	n/a	150psi	
KX125-L4													
120-140	10mm	0.40	100mm	5	16	12	4.7	97-100mm	12	10	2.5	150psi	
140-165	10mm	0.41	100mm	5	14	12	4.9	97-100mm	12	10	2.5	150psi	
165+	10mm	0.41	90mm	5	14	10	5.1	97-100mm	11	10	2.5	150psi	
KX250-L4													
130-145	12mm	0.42	100mm	5	14	10	4.9	98-100mm	12	10	2.5	150psi	
145-165	12mm	0.43	90mm	5	12	8	5.1	98-100mm	12	10	2.5	150psi	
165-180	12mm	0.43	90mm	5	12	6	5.3	98-100mm	11	10	2.5	150psi	
KX500-E14													
145-160	Std	0.39	100mm	5	10	6-8	5.3	100mm	8	12	n/a	150psi	
160-175	Std	0.40	100mm	5	10	6-8	5.5	100mm	8	12	n/a	150psi	
175+	Std	0.41	100mm	5	10	6-8	5.7	100mm	8	12	n/a	150psi	
KDX200-HB & KDX220-A9													
135-150	Std	0.34	95mm	5	n/a	8-10	4.8	100mm	9	10	n/a	150psi	
150-170	Std	0.35	95mm	5	n/a	8-10	5.0	100mm	9	10	n/a	150psi	
170-200	Std	0.36	95mm	5	n/a	8-10	5.2	100mm	9	10	n/a	150psi	
200+	Std	0.37	95mm	5	n/a	8-10	5.4	100mm	9	10	n/a	150psi	
KLX300-A7													
All weights	Std	0.38	95mm	5	n/a	14	5.8	100mm	9	12	n/a	150psi	

\*Fork Height is measured from top of fork tube to top of fork clamp.  
 \*\*Stock 86.3mm pull rods on the 2002 KX65 can be exchanged for optional 85.3mm or 87.3mm to raise or lower the seat height by 4.5mm each.  
 \*\*\*High speed compression adjuster is the outside 17mm adjuster nut on the shock. It has no detents.  
 \*\*\*\*Refer to the 2002 KX65 owners manual for position information.  
 FOOTNOTES - Rebound and compression adjustments are the number of clicks out from full hard (all the way in). Front fork oil level is measured in millimeters (mm). Rear shock sag level is measured in millimeters (mm). All optional spring part numbers can be found at your local Kawasaki dealership. SPECIAL NOTE - Team Green recommends that any suspension setting changes be done at normal riding temperatures. Always test new settings before racing. \*Team Green Specifications subject to change.